



CM30

Please note that the images are for illustrative purposes only. The final product may vary in design, features or specifications.

CM30 is designed for workshop use. CM30 is manually operated and easy to use and it comes with a fume exhaust connection.

3-phase and 1-phase electric configurations available. Please also see product cards for other CM30/35 configurations.


ABSOLUTE
QUALITY
MADE IN
FINLAND

| TECHNICAL DATA | |
|-------------------------------------|----------------|
| Max. hose size (inch) ¹⁾ | 2 / 1 ¼ |
| Diameter (blade) external (mm) | 300x3 |
| Diameter (blade) internal (mm) | 30 |
| Max. hose OD (mm) | 70 |
| Exhaust outlet OD (mm) | 60 |
| Motor Power (kW) ²⁾ | 3.0/2.2 |
| Motor Power (HP) ²⁾ | 4.0/2.9 |
| Velocity, 50Hz (rpm) | 2750 |
| Velocity, 60Hz (rpm) | 3370 |
| DIMENSIONS (LxWxH) | |
| mm | 600x503x739 |
| inch | 23.6x19.8x29.1 |
| WEIGHT | |
| kg/lbs | 42/92.4 |

MOTOR BRAKE
CM30B is equipped with mechanical brake for faster stopping of blade rotation.

PNEUMATIC PUSHER
CM30P is equipped with pneumatically operated hose pusher.

| MODELS |
|-------------------------------|
| Standard |
| CM30B |
| CM30P |
| STANDARD FEATURES |
| Toothed blade (part no 12297) |
| OPTIONS |
| Smooth blade (part no 12319) |



Toothed blade as a standard feature.



Smooth blade as an option.

Power supply cable not included.

1) Hydraulic hose, 1-2 wire / 4 wire
2) 3-phase / 1-phase