



Please note that the images are for illustrative purposes only. The final product may vary in design, features or specifications.

## CM75

Finn-Power CM75 hose-cutting machine has been designed to cut up to 2" diameter 6-spiral hoses. The hose is pushed against the blade by a pneumatic pusher.

Pusher movement speed can be quickly and easily adjusted to choose optimal cutting speed for every hose. The blade can be sharpened when necessary. The cutter has a built-in bin for collecting cutting waste.

SAFE- and QT-models also available.

ABSOLUTE  
QUALITY  
MADE IN  
FINLAND

### TECHNICAL DATA

Max. hose size (inch) <sup>1)</sup>	2
Diameter (blade) external (mm)	520x4
Diameter (blade) internal (mm)	38
Max. hose OD (mm)	71
Exhaust outlet OD (mm)	103
Motor Power (kW/HP)	7.5 / 10.0
Velocity, 50Hz (rpm)	2840
Velocity, 60Hz (rpm)	2840

1) Depending on hose type.

### DIMENSIONS (LxWxH)

mm	990x714x1318
inch	39.0x28.2x51.9

### WEIGHT

kg/lbs	300/485
--------	---------

Power supply cable not included.

### STANDARD FEATURES

- Toothed blade (part no 12251)
- Foot pedal (part no 701405)
- Adjustable pneumatic pusher speed
- Adjustable hose support

### OPTIONS

- Measuring table (2 m segments) (part no 692091)
- Fume extractor (part no 691992)
- Smooth blade (part no 055201)



Measuring table (left/right handed) as an option.