



CM30

CM30 is designed for workshop use. CM30 is manually operated and easy to use and it comes with a fume exhaust connection.

3-phase and 1-phase electric configurations available.

Please also see product cards for other CM30/35 configurations.

TECHNICAL DATA

Max. hose size (inch) ¹⁾	2 / 1 1/4
Diameter (blade) external	300x3
Diameter (blade) internal	30
Max. hose OD	70
Exhaust outlet OD (mm)	60
Motor Power (kW) ²⁾	3.0/2.2
Motor Power (HP) ²⁾	4.0/2.9
Velocity, 50Hz	2750
Velocity, 60Hz	3370

DIMENSIONS (LxWxH)

mm	600x503x739
inch	23.6x19.8x29.1

WEIGHT

kg/lbs	42/92.4
--------	---------

- 1) Hydraulic hose, 1-2 wire / 4 wire
2) 3-phase / 1-phase

STANDARD FEATURES


Toothed blade

OPTIONS

Smooth blade

Motor brake (CM30B)

Pneumatic pusher (CM30P)



Toothed blade
as a standard feature.



Smooth blade
as an option.

**FURTHER INFO ON OPTIONS,
PLEASE REVERT TO SPECIFIC PRODUCT CARD**

POWERCO.LILLBACKA.COM

J&E Machines B.V. Jacobus Lipsweg 100
3316 BP Dordrecht - The Netherlands
T: +31 (0)78 - 61 79 839
I: www.jemachines.nl - E: info@jemachines.nl