



P16HP, P16HPZ, P16AP, P16APZ

FAST AND RELIABLE FOR FIELD SERVICE REPAIRS

Finn-Power P16 series crimping machines are compact, strong and reliable for any service crimping need. Their compact design allows efficient working and easy transport between any locations. P16 machines are easy to use and they produce high quality crimping day after day.

J&E MACHINES
EXPERTS IN HIGH-TECH METALFORMING

+31 (0) 78 617 98 39 Jacobus Lipsweg 100
info@jemachines.nl NL-3316 BP Dordrecht

www.jemachines.nl

CONTROL

M MANUAL CONTROL

AVAILABLE MODELS

Z SEPARATED CRIMPING
HEAD AND BODY

HP HAND PUMP FOR EASY
FIELD SERVICE

AP AIR PRESSURE FOR EASY
FIELD SERVICE

DIE SET P16

Pno	Crimp. range	D	L
18212/10	10.0 - 12.0	10	55
18212/12	12.0 - 14.0	12	55
18212/14	14.0 - 16.0	14	55
18212/16	16.0 - 19.0	16	55
18212/19	19.0 - 23.0	19	55
18212/23	23.0 - 27.0	23	55
18212/27	27.0 - 31.0	27	65
18212/31	31.0 - 38.0	31	65

FEATURES

P16HP - PORTABLE

Manually operated hydraulic crimping machine for repair workshops. Easy to use, lightweight and compact in size.

P16HPZ - FLEXIBLE

Machine is connected to pump with a flexible hydraulic hose that enables crimping in tight and difficult spaces.

P16AP - COMPACT

Suitable for workshops where compressed air is available. This lightweight machine can easily be carried by hand in need of relocation.

P16APZ - FLEXIBLE

Machine is connected to pump with a flexible hydraulic hose that enables crimping in tight and difficult spaces.

DIE SETS

P16

P16

P16

P16

CRIMPING RANGE (MM) ⁽¹⁾

10 - 45

10 - 45

10 - 45

10 - 45

CRIMPING RANGE (INCH) ⁽¹⁾

0.39 - 1.77

0.39 - 1.77

0.39 - 1.77

0.39 - 1.77

MAX OPENING (MM)

+20

+20

+20

+20

MAX CRIMPING FORCE (KN)

955

955

955

955

MAX CRIMPING FORCE (TON.)

95

95

95

95

NUMBER OF CRIMPS/HOUR ⁽²⁾

—

—

—

—

PUMP

HAND PUMP

HAND PUMP

AIR PUMP

AIR PUMP

PUMP

HAND PUMP

HAND PUMP

AIR PUMP

AIR PUMP

WEIGHT (KG)

26

28

28

26

WEIGHT (LBS)





57

62

62

57

MEASUREMENTS



- With standard dies. Crimping range can be increased with special dies.
- Theoretical with 10 mm cycle.