





CM75QT is equipped with touch-control which enables connectivity and job queues.

CM75QT is also available as SAFE-model.

TECHNICAL DATA	
Max. hose size (inch) 1)	2
Diameter (blade) external (mm)	520x4
Diameter (blade) internal (mm)	38
Max. hose OD (mm)	71
Exhaust outlet OD (mm)	103
Motor Power (kW/HP)	7.5 / 10.0
Velocity, 50Hz (rpm)	2840
Velocity, 60Hz (rpm)	2840
DIMENSIONS (LxWxH) with 6	m table
mm	7134x1080x1330
inch	280.8x42.5x52.3
WEIGHT with 6m table	
ka/lbs	920/2024

1) Depending on hose type.



Toothed blade as a standard feature.



Smooth blade as an option.

ABSOLUTF QUALITY MADE IN FINLAND

Touchscreen		
Toothed blade ((part no 12251)	
Foot pedal		
Adjustable pne	umatic pusher speed	
Adjustable hose	e support	
Measuring table	e (6 metre)	
	e (2 m segments) (part no 692091)	
Measuring table	2 (2 m segments) (part no 692091)	
	e (2 m segments) (part no 692091) (part no 691992)	
Fume extractor		
Fume extractor Smooth blade ((part no 691992) part no 055201)	
Fume extractor	(part no 691992) part no 055201) E-model)	
Fume extractor Smooth blade (Safeguard (SAFI	(part no 691992) part no 055201) E-model) IFE-model)	
Fume extractor Smooth blade () Safeguard (SAFI Motor brake (SA	(part no 691992) part no 055201) E-model) IFE-model)	
Fume extractor Smooth blade () Safeguard (SAFI Motor brake (SA	(part no 691992) part no 055201) E-model) IFE-model)	



Power supply cable not included.





