



CM75 SAFE

Finn-Power CM75 SAFE has the same capacity as in CM75 with added safeguard and motor brake. Safeguard opens only after blade rotation has stopped.

Service free electrical brake stops the blade in only 3 seconds.

Pusher movement speed can be quickly and easily adj optimal cutting speed for every hose. The blade can be necessary. The cutter has a built-in bin for collecting co

See also QT-model.

TECHNICAL DATA	
Max. hose size (inch) 1)	2
Diameter (blade) external (mm)	520x4
Diameter (blade) internal (mm)	38
Max. hose OD (mm)	71
Exhaust outlet OD (mm)	103
Motor Power (kW/HP)	7.5 / 10.0
Velocity, 50Hz (rpm)	2840
Velocity, 60Hz (rpm)	2840
DIMENSIONS (LxWxH)	
mm	990x890x1318
inch	39x35x51.9
WEIGHT	
kg/lbs	340/748

ABSOLUTE QUALITY MADE IN FINLAND

y adjusted to choose an be sharpened when ng cutting waste.	STANDARD FEATURES Toothed blade (part no 12251) Foot pedal Adjustable pneumatic pusher speed Adjustable hose support Safeguard Motor brake
1) Depending on hose type.	OPTIONS Measuring table (2 m segments) (part no 692091) Fume extractor (part no 691992) Smooth blade (part no 055201)
•	y de la constant de l
	Measuring table (left/right handed) as an option.



Power supply cable not included.





